

Solving challenges in the hospital with the right technology. Technology has long played an imperative role in streamlining hospital operations and improving patient care. Healthcare personnel need to be assured that each image, or streaming images, being viewed are an accurate depiction of the tissue and bone being studied.

Designed for surgical suites demanding reliability and the latest technology.




































Mechanical Drawing







Ground pad
 Switch
 24 DC in
 Dual DVI in

5. HDMI 1.4

6. DP 1.2 Out

- 7. DP 1.2 In 8. VGA In 9. HDMI 2.0 10. SDI in 11. SDI out 12. RJ-11
- 14. Line Out 15. RS-232 16. USB 2.0

17. Power 5V Out

Product Specifications

Screen Technology	LED Backlight Technology, TFT Active-matrix,	
· · · · · · · · · · · · · · · · · · ·	Widescreen, IPS Technology	
Viewable Size	27" diagonal	
Active Area	596.16 (H) x 335.34 (V) mm	
Native Resolution	3840 x 2160 (UHD 4K)	
Pixel Pitch	155.25 (H) x 155.25 (V) um	
Aspect Ratio	16:9	
Response Time	12ms (Gray to Gray)	
Light Intensity	300 cd/m²	
	700cd/m² (Optional)	
Contrast Ratio	1000:1 (typ)	
View Angle	89/89/89/89	
Max Colors	1.07B	
Touch	Projected Capacitive Touch, USB interface	
	AR Glass (Optional)	
Color Profiles	Support 3D LUT profile	
	6 x general user color schemes	
	DICOM GSDF (Optional)	
Product Features	Ambient light sensor	
	IR Control	
	Internal Backlight sensor (Optional for 700 cd/m	
Power Specifications	24V DC in 150W, with external	
•	110-240V AC to DC Adapter	
User Controls and	Capacitive OSD :	
Activity	Power On/Off, On Screen Display Menu,	
	Brightness Control (-/+)	

Input Signal	• 3G SDI*	• VGA	
	• HDMI 2.0	 Dual DVI in 	
	• DP 1.2	• HDMI 1.4	
	Audio In		
Output Signal	• DP (Multi-Stream Transport)		
	Audio Out		
	• 5V out		
	• 3G SDI (Loop Thr	ough), support 1080P*	
Product Dimensions	643.17 x 408.06 x 48 mm (25.3 x 16.1 x 1.8 in)		
Mounting	VESA mounting 100 x 100mm		
	VESA mounting 200 x 100mm		
Product Weight	9.5 Kg (20.9 lbs)		
Housing	Antimicrobial Surface Coating		
Operating Temperature	0 deg.C to 35 deg.C, Humidity up to 95%		
Storage Temperature	-20 deg.C to 60 deg.C, Humidity up to 95%		
IP Rating	Protection: front IP65 - rear IP22		
Type Approval,	• IEC 60601-1:2005 + A1:2015 (Ed. 3.1)		
Testing and Certificates	• IEC 60601-1-6:2010 + A1:2013 (Ed. 3.1)		
	• IEC 62366:2007 + A1:2014 (Ed. 1.1)		
	ANSI/AAMI ES60	601-1:2005/	
	A1:2012 and C1:2009/(R)2012 and A2:2010/(R)2012		
	• CAN/CSA-C22.2 No.60601-1:14		
	• EN606001-1-2		
	• EN55032/EN55024, FCC part 15B		
	• EN60950-1		
	• RoHS-2, REACH,	WEEE compliant	
	CE F©	L) us	